

# MECHANICAL PRODUCTS CATALOGUE





# MECHANICAL PRODUCTS

ARG 235 Plus Band saw	04	Button bits flat-end type			
machine		Button bits sunken-head type	10		
Rotary drill bits	06	Button bits auxiliary-cutting	10		
Chisel bits type	08	edge type	10		
Cross bits type	08	Coal cutting bits	12		
Coal lauger type	09	13-43H holder	12		
Down-the-hole hammer bits	09	13-375 holder	12		
Button bits Ø42 type	10	Hard alloy products	13		

# **ARG 235 PLUS BAND SAW MACHINE**

#### **PRODUCT DESCRIPTION**




ARG 235 Plus Band saw machine can cut materials up to 235mm in diameter, featuring a sturdy cast iron frame that reduces vibration and enhances durability. Equipped with a three-phase, dual-speed motor (40 and 80 rpm), this machine enables precise cutting of various materials including stainless steel and tool steel.

#### **TECHNICAL SPECIFICATIONS**


Engine power	400 V, 50Hz, 0,9/1,4 kW
Pump capacity	400 V, 50Hz, 0,05 kW
Saw blade speed	40/80 m/min
Maximum workpiece he	ight 900 mm
Coolant tank capacity	cca 15 I
Machine dimensions (Minimum)	1640 x 750 x 1400 mm
Machine dimensions (Maximum)	1930 x 1610 x 2000 mm
Weight	295 kg



















#### **PRODUCT DESCRIPTION**

Rotary bit borers are designed and produced by combining the borers of Russia, China, Japan and Sweden. Such products can operate efficiently on the rocks whose coefficient of hardness reaches F14.

Shots are made of Cacbit Vonfram hard alloy with high quality and the bearing of bending strength, fatigue streng and abrasivity.

The products are used to bore the rocks and soils as follows: Granit, Quatz Pocgia, Silicon shale, Cacket, limestone, grit, quatz ore, Dolomite and sandstone whose hardness is up to F14.







+ SPECIFICATIONS	D (mm)	L (mm)	Connecting thread
13-MKXC-200	200	336	API 4 1/2 Reg
13-MKXC-230	230	345	API 41/2 Reg
13-MKXC-250	250	341	API 6 5/8 Reg







## **CHISEL BITS TYPE**

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>Weight</b> kg
13-N1-32/20	32	20	68	0,26
13-N1-36/22	36	22	71	0,32
13-N1-38/22	38	22	73	0,35
13-N1-38/24	38	24	73	0,35
13-N1-40/22	40	22	73	0,38
13-N1-40/24	40	24	73	0,38
13-N1-42/22	42	22	73	0,40
13-N1-42/24	42	24	73	0,40



## CROSS BITS TYPE

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>Weight</b> kg
13-T-42/42	42	24	73	0,47
13-T-38/22	38	22	73	0,40
13-T-36/22	36	22	71	0,36
13-T-36/20	36	20	71	0,30





# COAL LAUGER BITS

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>a</b> deg	<b>β</b> deg	<b>Weight</b> kg
13-42A	42	16,5	80	9	5	0,25
13-42B	42	11,5	84	_	_	0,25



#### **DOWN-THE-HOLE HAMMER BITS**

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>Weight</b> kg
13-110	110	52	180	4,4
13-110H	110	52	182	4,4
13-130	130	52	193	7,2



#### **BUTTON BITS Ø42 TYPE**

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>Weight</b> kg	
13-42H-R25	42	25	96	0,56	
13-42H-24	42	24	84	0,56	



#### **BUTTON BITS FLAT-END TYPE**

Kiểu, loại	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	Khối lượng kg
13-76B-T38	77	38	135	2,5
13-89B-T38	89	38	140	3,6
13-89B-T45	89	45	140	3,2
13-102B-T38	102	38	155	5,3
13-102B-T45	102	45	155	5,0
13-102B-T51	102	51	155	4,6



#### **BUTTON BITS SUNKEN-HEAD TYPE**

Туре	<b>D</b> mm	<b>d</b> mm	<b>L</b> mm	<b>Weight</b> kg
13-T-42/42	102	38	156	4,7
13-T-38/22	102	45	156	4,9
13-T-36/22	102	51	156	4,85
13-T-36/20	105	51	156	6,0



#### **BUTTON BITS AUXILIARY-CUTTING EDGE TYPE**

Туре	<b>D</b>	<b>d</b>	<b>L</b>	<b>Weight</b>
	mm	mm	mm	kg
13-102LF-T45	102	45	170	7,0
13-127LF-T58	127	58	203	11,8






## **COAL-CUTTING BITS**





#### **13-43H HOLDER**



## 13-375 HOLDER





# **HARD ALLOY PRODUCTS**

**EMPLOYING AUTOMATED** PRESSING AND VACUUM **SINTERING PROCESSES** 





#### **PRODUCTS TYPE**

Metal shears labeled ZT15, ZT798, ZA1... have high strength and hardness as well as can bear strong vibration, collision and friction. Meanwhile, such products are well known for their high hot rigidity and heat resistance.

Blades and cutting particles for the borers labeled ZC8, ZC11, ZC11T, ZC13, ZC13T... which are used to exploit rocks and ores with the hardness up to F14, including the borers whose diameters are Ø32, Ø36, Ø38, Ø42, Ø110, rotary bit borers Ø200, Ø230, Ø250.... Producing coal borers and Coal-cutting bits with high strength.

Stamping and broaching mortars labeled ZC6, ZC8, ZC11M... own a strength and hardness many times higher than that of steel mortars.

Shaped products in accordance with the orders.







# 13 MECHANICS AND CHEMICALS ONE MEMBER LIMITED LIABILITY COMPANY

Address Group 22, Doi Can Ward, Tuyen Quang City

Phone (0207) 3 878 103 - (0207) 3 878 104

Fax (0207) 3 878 102

Website z113.vn Email info@z113.vn

